

Microalgae cultivation as a tertiary treatment step in urban wastewater treatment plants

S.A. Vaz^{1,2*}, R.C. Martins², H.M. Pinheiro³, L.P. Monteiro¹

¹ A4F - Algae For Future SA, Campus do Lumiar, Edifício E - R/C, Estrada do Paço do Lumiar, 1648-038 Lisboa, Portugal; ² University of Coimbra, CERES, Department of Chemical Engineering, FCTUC, Pólo II, 3030-790 Coimbra, Portugal; ³ iBB—Institute for Bioengineering and Biosciences and Department of Bioengineering, Instituto Superior Técnico, Universidade de Lisboa, Av. Rovisco Pais, 1049-001 Lisboa, Portugal; * sofia.vaz-ext@algafuel.pt.

Introduction and Aim

The revised urban wastewater treatment directive demands tertiary treatment for plants treating 150.000 p.e. or above. Microalgae cultivation shows great promise for this purpose, allowing not only to remove but also to recover N and P, contributing to the circular economy. The aim of this work is to optimize the hydraulic retention time (HRT) in microalgae-based processes to recover nutrients from urban wastewaters.


Methodology

Reactor type: Pilot scale conventional raceway system.
Nº reactors: 2, one operated as control and one for tests.
Conditions tested: HRT=7 days (control), HRT=4 and 5.5 days (test).
Working volume: 700 L **Photosynthetic area:** 5 m²
Operation mode: Semi-continuous.
Operation time: Between 27/12/2023 and 25/03/2024 (winter season).
Nº of treatment cycles: HRT=4 days - 15, HRT=5.5 days - 13 and HRT=7 days - 25
Culture media: Secondary effluent from a wastewater treatment facility receiving urban and industrial wastewater.




Results


Biomass




Nitrogen




Phosphorus




Typical cycle variation



Carbon



Environment



Concluding remarks

- The microalgae treatment revealed to be **effective and robust for tertiary treatment**, even during the harshest season (winter).
- The final levels achieved for nitrogen and phosphorus were **compliant with the new European Directive demands** in most studied conditions.
- Inorganic carbon was removed from the wastewater as well as from the environment leading to a **negative carbon footprint**.

Acknowledgments: S.A. Vaz acknowledges the doctoral grant with the reference PRT/BD/152859/2021 from FCT - Fundação para a Ciência e a Tecnologia, I.P. The authors acknowledge further support from FCT through institutional grants (UIDB/EQU/00102/2020, UIDB/04565/2020, UIDP/04565/2020, LA/P/0140/2020). The authors acknowledge Águas do Tejo Atlântico for essential technical collaboration. This project has received funding from the European Union's Horizon Europe research and innovation programme under grant agreement No 101144144.